Chapter 12
Between Relational Data and XML

Data integration between “Legacy Systems” and XML databases

- Note: “legacy” now means SQL ...

Mixing everything up ...

Access to data stored in relational databases by

- using an XML environment (e.g., saxon) and mapping relational data from a remote SQL database (e.g. Oracle) to XML, and working with it.
- using XML-world concepts and languages in an SQL environment, e.g. for exchanging data in XML format (again, e.g., Oracle).

(Note that IBM DB2/XML Extender and MS SQL Server provide similar functionality)

12.1 Publishing/Mapping Relational Data in XML

Several *generic* mappings are possible:

Consider country(name: “Germany”, code: “D”, population: 83536115, area: 356910)

- tables, rows, and subelements

```
<table name="country">
 <row><name>Germany</name><code>D</code>
      <population>83536115</population><area>356910</area></row>
    :
</table>
```

- tuples with subelements

```
<country><name>Germany</name><code>D</code>
         <population>83536115</population><area>356910</area></country>
    :
```

- analogous with XML attributes
- advantage with subelements (vs. attributes): SQL values can also be object types (mapped to XML) and XMLType contents!

Example: HTTP-based access to Oracle

The whole database is mapped (virtually) to XML:

```
<SCHMIDT>   -- user name as root element
  <COUNTRY>  -- all names are capitalized
    <ROW><NAME>Germany</NAME><CODE>D</CODE>
      <POPULATION>83536115</POPULATION><AREA>356910</AREA></ROW>
    :
  </COUNTRY>
  :
</SCHMIDT>
```

Access by extended URL notation:

- URL: *computer*:*port*/oradb/*user*/*tablename*/ROW[*condition*]
- capitalize user, table and attribute names
- URL must select a single element (whole table, or single row)

```
ap34.ifi...:8080/oradb/DUMMY/COUNTRY            %% show page source
ap34.ifi...:8080/oradb/DUMMY/COUNTRY/ROW[CODE='D']
ap34.ifi...:8080/oradb/DUMMY/COUNTRY/ROW[CODE='D']/NAME
ap34.ifi...:8080/oradb/DUMMY/COUNTRY/ROW[CODE='D']/NAME/text()
```


Generic Mappings (Cont'd)

Up to now: mapping of materialized base tables.
Problem: how to map the result of a query with computed columns?
`SELECT Name, Population/Area FROM country`

- tables, rows, and subelements:
  the DTD is independent from the relational schema
  metadata is contained in the attributes
  ("JDBC-style" processing of result sets)

```
<table name="country">
  <row><column name="name">Germany</column>
       <column name="population/area">83536115</column>
       <column name="area">234.05473</column>
  </row>
   :
</table>
```

- another "most generic mapping" as (object, property, value) to be discussed later ...

Additionally: often, tools define their own access functionality ...

Access to SQL Databases with saxon-XSLT

[does currently not work]

- uses JDBC technology for remote access (at least for Java XSL tools)
- defines namespace “sql”
- <sql:connect> with attributes “database” (JDBC url), “driver” (JDBC driver)
  returns a JDBC connection object as a value of type “external object” that can be bound to a variable, e.g. $connection.
  Note: there can be several connections at the same time.
- <sql:query> with following attributes allows to state an SQL query whose result is generically mapped to XML:
  - connection
  - table: ... the “FROM” clause
  - column: ... the “SELECT” clause
  - where: optional condition
  - row-tag: tag to be used for rows (default: “row”)
  - col-tag: tag to be used for columns (default: “col”)

  result is a collection of <row> ... </row> elements that can e.g. be bound to a variable.

Administrative Parameters

```
<xsl:stylesheet xmlns:xsl="http://www.w3.org/1999/XSL/Transform" version="2.0"
  xmlns:sql="java://net.sf.saxon.sql.SQLElementFactory">

<!-- insert your database details here, or supply them in parameters -->
<xsl:param name="driver" select="'oracle.jdbc.driver.OracleDriver'"/>
<xsl:param name="database" select="'jdbc:oracle:thin:USER/PASSWD@IPADDRESS:1521:USER'"/>
<xsl:param name="user" select="'USER'"/>
<xsl:param name="password" select="'PASSWD'"/>

<xsl:variable name="connection" as="java:java.sql.Connection"
      xmlns:java="http://saxon.sf.net/java-type">
  <sql:connect xsl:extension-element-prefixes="sql"
      driver="{$driver}" database="{$database}"
      user="{$user}" password="{$password}">
    <xsl:fallback>
      <xsl:message terminate="yes">SQL extensions not installed</xsl:message>
    </xsl:fallback>
  </sql:connect>
</xsl:variable>
</xsl:stylesheet>
```

[Filename: XSLT/sql-administrativa-fake.xsl]

Example Access/Query

```
<xsl:stylesheet xmlns:xsl="http://www.w3.org/1999/XSL/Transform" version="2.0"
  xmlns:sql="java:/net.sf.saxon.sql.SQLElementFactory">
<xsl:include href="sql-administrativa.xsl"/>

<xsl:template match="*">
  <xsl:call-template name="countries"/>
</xsl:template>

<xsl:template name="countries">
 <xsl:variable name="country-table">
   <!-- ** the query's result is bound to the surrounding variable ** -->
   <sql:query xsl:extension-element-prefixes="sql"
        connection="$connection" table="country" column="*"/>
 </xsl:variable>
 <xsl:copy-of select="$country-table"/>
 <sql:close connection="$connection"/>
</xsl:template>
</xsl:stylesheet>
```

[Filename: XSLT/sql-query.xsl]

uses a primitive mapping that relies on the order of columns.

Example Access/Query

```
<xsl:stylesheet xmlns:xsl="http://www.w3.org/1999/XSL/Transform" version="2.0"
  xmlns:sql="java:/net.sf.saxon.sql.SQLElementFactory"
  extension-element-prefixes="sql">
<xsl:include href="sql-administrativa.xsl"/>

<xsl:template match="*">
 <xsl:call-template name="countries"/>
</xsl:template>

<xsl:template name="countries">
 <xsl:variable name="country-table">
   <sql:query connection="$connection" table="country,encompasses"
       where="country.code=encompasses.country"
       column="country.name,encompasses.continent,percentage"
       row-tag="country" column-tag="bla"/>
 </xsl:variable>
 <xsl:copy-of select="$country-table"/>
 <sql:close connection="$connection"/>
</xsl:template>
</xsl:stylesheet>
```

[Filename: XSLT/sql-query2.xsl]

Further Commands

- <sql:insert> with attribute
  - attribute: table="..."
  - children: <column name="..." select="..."/>
    value can also be given as contents of the column element; currently always interpreted as a string.
- <sql:close> with a "connection" attribute

See also `http://www.saxonica.com/documentation/documentation.html`

12.2 The SQL/XML or SQLX standard

Goal: Coexistence between Relational Data and XML

- mapping relational data to XML
  - by a default mapping (previous section)
  - a (user-defined) XML views over relational data
    ("XML publishing")
- storing XML data in relational systems
  - data-centric XML: efficient, several possibilities
  - document-centric XML: problematic

SQL/XML

- draft for an ISO standard since 2003: `www.sqlx.org`
- an SQL datatype "XMLType" for storing XML as "value" in databases:

  Jim Melton (Oracle): *"SQL/XML includes an XML datatype for use inside SQL. This allows the SQL engine to automatically 'shred' data-oriented XML documents for storing some elements and contents in one place while keeping other elements in other places. Using indexes and joins, you can then bring this data back together very quickly."*

  – theory: an abstract datatype with operators/methods
    (cf. Computer Science I lecture)
  – API: like (user-defined) object types in object-relational databases
    (cf. SQL database lab)
    * handled with special methods (constructors, selectors)
    * can be exported to XML tools, e.g. by JDBC
      (either as DOM instance, or *serialized* as ASCII)
    * libraries provide additional functions for processing XML in PL/SQL.
  – internal implementation: not seen by the user
    (i) shredding or (ii) storing as LOB (Large Object)

SQL/XML

Making XML data a first-class citizen in relational databases,
seamless flow from relational data to XML and back

SQL to XML

- XML generation from SQL queries (i.e., in the SELECT clause)
  (e.g., as packets for data exchange)
- define XMLType views over SQL data

SQL access and manipulation of XML inside the RDB

... use XPath expressions inside SQL (and rise the question what is actually the difference to XQuery):

- storing XML in RDB (e.g. if XML-data exchange packets came in),
- XPath-based extraction of XML content (SELECT clause),
- XPath-based query of XML content (WHERE clause),
- XPath-based update of XML content (in SQL),
- define XPath-based relational views over XML content.

"XML" AS AN SQL DATATYPE

XML/XMLType: an *SQL* datatype to hold XML data:

CREATE TABLE Mondial OF XMLType; use as Row Object Value
CREATE TABLE CountryXML OF XMLType; use as Row Object Values

As red column object type in relational tables:

```
CREATE TABLE CityXML
  (name XMLType,  province VARCHAR2(32),  country VARCHAR2(3),
   population XMLType,
   coordinates XMLType);
```

[Filename: SQLX/cityxmltable.sql]

- generation: INSERT INTO *table* VALUES (... , XMLType('*XML as ASCII*') ...)

```
INSERT INTO CityXML
VALUES(XMLType('<name>Clausthal</name>'), 'Niedersachsen', 'D',
 XMLType('<population year="2004">10000</population>'),
 XMLType('<coordinates><longitude>10.4</longitude><latitude>51.8</latitude>
          </coordinates>'));
```

[Filename: SQLX/cityxmltuple.sql]

HANDLING OF SQL XMLTYPE DATATYPE

- generate it by certain *constructors* ("XML Publishing Functions")
- storage: chosen by the database
  - "shredding" and distributing over suitable tables (of object-relational object types) (queries are translated into SQL joins/dereferencing)
  - storing it as VARCHAR, CLOB (Character Large Object), or as separate file (the remainder of this section uses CLOB)
  - storing it "natively"
- query it by XPath
- export/exchange in ASCII:
  XMLSerialize: a function to serialize an XML value as an ASCII character string:
  XMLSerialize: XMLType → String
- additional methods provided by PL/SQL libraries,
- XML objects can also be used e.g., as documents or as stylesheets, applied to documents (by PL/SQL libraries).

How to get XMLType Instances

- by the *opaque* constructor
  XMLType: STRING → ELEMENT
  that generates an XMLType instance from an ASCII string
  - the inverse to Java's `to_string`,
  - nearly all datatypes have such an opaque constructor (e.g., for lists: list("[1,2,3,4,5]"));
- generate instances recursively by structural constructors that are closely related to the underlying *Abstract Datatype*
  (cf. binary trees, lists, stacks in Computer Science I);
- or load them from an XML file (that then actually contains the ASCII serialization and uses the opaque constructor).

Loading XMLType Instances

- from files:
  - tell Oracle where it finds XML files:

    ```
    CREATE OR REPLACE DIRECTORY XMLDIR AS '/tmp/' ;
    ```

    * Admin only, or after GRANT CREATE ANY DIRECTORY,
    * on the same computer where the DBMS server (!) is installed.
  - copy XML file (e.g. m.xml) into XMLDIR
    * Note that the XML file must not contain a reference to a DTD!
    * note that the file must be publicly readable – `chmod` $filename$ `644`
  - load the file into the database (use the xdb_utilities package)

    ```
    INSERT INTO mondial VALUES(xdb_utilities.getXMLfromfile('m.xml','XMLDIR'));
    set long 10000 ;   -- number of characters in the output
    SELECT * FROM mondial;
    ```

Admin's Note on Creating Directories

```
admin: GRANT CREATE ANY DIRECTORY TO scott;
scott: CREATE  OR REPLACE DIRECTORY XMLDIR AS '/tmp';
SELECT owner, object_name FROM all_objects WHERE object_type='DIRECTORY';
SELECT * FROM all_directories;
```

- The directory belongs then to SYS
- there is only one such directory declaration for the whole system
- "delete" it (i.e., make it unknown) `DROP directory XMLDIR`
- allow users to use the directory for reading:

```
GRANT READ on XMLDIR TO scott;
```


LOADING XML FILES: LOCAL SOLUTION

- for importing XML files, our local installation provides a method `system.getxml('`*http-url*`')`:

```
SELECT system.getxml(
  'http://www.dbis.informatik.uni-goettingen.de/Teaching/DBP/XML/mondial.xml')
FROM dual;
```

or, inserting it into a table:

```
INSERT INTO mondial VALUES(
 system.getxml(
  'http://www.dbis.informatik.uni-goettingen.de/Teaching/DBP/XML/mondial.xml'));
```

[Filename: SQLX/insertmondial.sql]

- Note that the XML file must not contain a reference to a DTD!
- the file can e.g. reside in the local homedirectory or anywhere in the Web,
- note that the file must be publicly readable – `chmod` *filename* `644`

```
SET LONG 10000;
SELECT * FROM mondial;
```

SQL/XML: Generating XML by XML Publishing Functions

The SQL/XML Standard defines “XML publishing functions” that act as constructors (the name comes from the fact that they are also used to publish relational data in XML format):

- constructors of the recursively defined abstract datatype “XMLType”,
- create fragments or instances of XMLType,
- usage in the same way as predefined or user-defined functions (e.g., in the SELECT clause),
- output (e.g. in SELECT) in ASCII notation.

Some Theory: the Abstract Datatype

... constructors of the recursively defined abstract datatype “XMLType”:

Sub-datatypes:

- ELEMENT for element nodes
- ATTRIBUTE for attribute nodes
- QNAME for names of elements and attributes
  (restriction of STRING without whitespaces etc.)
- STRING for text values (text nodes and attribute values)
- TUPLE(*type*) for a tuple of instances of *type*
- TABLE(*type*) for a table of instances of *type*

Constructors are very similar to those of XQuery (in the return clause), e.g.,:

```
element name attrs-and-content
```

and those of XSLT: `<xsl:element name="...">` *content* `</xsl:element>`
and those of the ... DOM.

(always the same abstract datatype, but expressed with different syntaxes)

SQL/XML Publishing Functions: Overview

Basic constructors:

- XMLType: generates an XMLType instance from an ASCII string (“opaque constructor”)
  XMLType: STRING $\rightarrow$ ELEMENT
- XMLElement: generates an XML element with a given name and content (either text (simple contents) or recursively created XML (complex contents) or mixed
  XMLElement: QNAME $\times$ (STRING $\cup$ ELEMENT $\cup$ ATTRIBUTE)* $\rightarrow$ ELEMENT
  XMLElement: QNAME $\rightarrow$ ELEMENT for empty elements
- XMLAttributes: generates a one or more attribute nodes from a sequence of name-value-pairs
  XMLAttributes: (QNAME $\times$ STRING)$^+$ $\rightarrow$ ATTRIBUTE$^+$

SQL/XML Publishing Functions: Overview (Cont’d)

Further constructors:

- XMLForest: a function to generate a sequence, called a ”forest,” of XML elements with simple contents from a *sequence* of name-value-pairs
  XMLForest: (QNAME $\times$ STRING)$^+$ $\rightarrow$ ELEMENT$^+$
  (note: the analogue to XMLAttributes for simple elements)
- XMLAgg: a function to group, or aggregate, XML data in a table into a sequence of nodes
  XMLAgg: TABLE(XMLTYPE) $\rightarrow$ XMLTYPE*
  (note that a table is different from a list as in XMLForest!)
- XMLConcat: a function to concatenate the components of a tuple into a sequence
  XMLConcat: TUPLE(XMLTYPE$^+$) $\rightarrow$ XMLTYPE*
  (note that a tuple is also different from a list as in XMLForest!)
- [XMLNamespaces: a function to declare namespaces in an XML element]

CONSTRUCTING XML: ELEMENTS

Basic form: XMLElement

- XMLElement: Name $\times$ Element-Body $\rightarrow$ Element:
  - Element-Body: text or recursively generated (attributes, elements, mixed)

```
SELECT XMLElement("x") FROM DUAL;
```

(note: this result is not correct: <x/> is an empty Element, while <x></x> is an element with the empty string as contents!)

```
SELECT XMLElement("Country",'bla') FROM DUAL;
SELECT XMLElement(Country,'bla') FROM DUAL;
```

- note: using "..." to indicate non-capitalization (otherwise the whole name is capitalized). (note that single and double "..." must be used exactly as in the example).

Elements with Non-Empty Content

- XMLElement: second argument contains the element body (attributes, subelements, text),
- XMLAttributes: list of name-value pairs that generate attributes.

```
SELECT XMLElement("Country",
  XMLAttributes(code AS "car_code", capital AS "capital"),
  name,
  XMLElement("Population",population),
  XMLElement("Area",area))
FROM country
WHERE area > 1000000;
```

[Filename: SQLX/xmlelement.sql]

A result element:

```
<Country car_code="R" capital="Moscow">
  Russia
  <Population>148178487</Population>
  <Area>17075200</Area>
</Country>
```

Optional Substructures

- XML as abstract datatype, *functional* constructors
- semistructured data: flexible and optional substructures

```
SELECT XMLElement("City",
  XMLAttributes(country AS country),
  XMLElement("Name",name),
  CASE WHEN longitude IS NULL THEN NULL
       ELSE XMLElement("Longitude",longitude) END,
  CASE WHEN latitude IS NULL THEN NULL
       ELSE XMLElement("Latitude",latitude) END)
FROM city
WHERE longitude IS NOT null;
```

[Filename: SQLX/xmlelement2.sql]

- Note: `CASE WHEN` $cond$ `THEN` a `ELSE` b `END`
  is a *functional* construct
  (like in "`if`" in XQuery and `<xsl:if>` in XSLT)

CONSTRUCTING XML: SEQUENCES OF ELEMENTS

XMLForest: short form for simple elements

```
SELECT XMLElement("Country",
          XMLForest(name AS Name,
                    code AS car_code,
                    population AS "Population",
                    area AS "Area"))
FROM country
WHERE area > 1000000;
```

[Filename: SQLX/xmlforest.sql]

```
<Country>
  <NAME>Brazil</NAME>              <!-- note capitalization -->
  <CAR_CODE>BR</CAR_CODE>
  <Population>162661214</Population>
  <Area>8511965</Area>
</Country>
```

$\Rightarrow$ canonical mapping from tupels to XML elements with simple content.

Subqueries

Contents can also be generated by (correlated) Subqueries:

```
SELECT XMLElement("Country",
         XMLAttributes(code AS "car_code"),
         XMLElement("Name",name),
         XMLElement("NoOfCities",
                    (SELECT count(*)
                     FROM City
                     WHERE country=country.code)))
FROM country WHERE area > 1000000;

SELECT XMLElement("Country",
         XMLAttributes(code AS "car_code"),
         XMLElement("Name",name),
         (SELECT XMLElement("NoOfCities",count(*))
          FROM City
          WHERE country=country.code))
FROM country WHERE area > 1000000;
```

[Filename: SQLX/xmlsubquery.sql]

CONSTRUCTING XML: RESTRUCTURING

- Relational databases have
  - literals (and objects for object-relational tables),
  - tuples,
  - tables.
- XML structures have
  - sequences
  - nesting (generated by XMLElement or by nested subqueries)

How to create

- a sequence from a tuple [note: XMLForest does not create a sequence from a tuple, but from a list that is generated from a tuple], or
- a sequence from a table?

CONSTRUCTING XML: GROUPING INTO A SEQUENCE

Aggregated Lists

- XMLAgg: is a new SQL aggregate function (like `count()` or `sum()`), that does not return a single value but the sequence of nodes of that table
- Note: XMLAgg is not applied to a *sequence* of items, but to a *table* of items!

Simplest case: XMLAgg over a table of XMLType row objects:

```
SELECT XMLElement("Cities",
  (SELECT XMLAgg(name)
   FROM CityXML c))
FROM DUAL;
```

[Filename: SQLX/xmlagg.sql]

Result:

```
<Cities>
  <name>...</name>
  <name>...</name>
  :
</Cities>
```


CONSTRUCTING XML: GROUPING

Aggregated Lists

... another example

- create a sequence of XML nodes from all entries of a relational table:

```
SELECT XMLElement("Continents",
  (SELECT XMLAgg(XMLElement("Continent", XMLAttributes(name AS "Name",
                                                       area AS "Area")))
   FROM continent))
FROM DUAL;
```

[Filename: SQLX/xmlagg2.sql]

Result:

```
<Continents>
  <Continent Name="Europe" Area="..."/>
  <Continent Name="Asia" Area="..."/>
  :
</Continents>
```

CONSTRUCTING XML: NESTED GROUPING

Grouping/Aggregation: Nested Lists

- XMLAgg: generate a collection from the tuples inside of a GROUP BY:
  In XML, this *list* of items can also be used!

... now we can have the number of cities in a country, together with a list of them:

```
SELECT XMLElement("Country",
        XMLAttributes(country AS car_code),
        XMLElement("NoOfCities", count(*)),
        XMLAgg(XMLElement("city",name) ORDER by population))
FROM city
GROUP BY country;
```

[Filename: SQLX/xmlgroupagg.sql]

Element of the result set:

```
<Country CAR_CODE="D">
  <NoOfCities>85</NoOfCities>
  <city>Erlangen</city> <city>Kaiserslautern</city> ... <city>Berlin</city>
</Country>
```


CONSTRUCTING XML: MAPPING TUPLES INTO SEQUENCES

XMLConcat

- takes a tuple of XML elements and transforms them into a sequence:

```
SELECT XMLElement("City", XMLConcat(name, population, coordinates))
FROM CityXML
WHERE country='D';
```

[Filename: SQLX/xmlconcat.sql]

An element of the result set:

```
<City>
 <name>Berlin</name>
 <population>...</population>
 <coordinates><longitude>...</longitude><latitude>...</latitude></coordinates>
</City>
```

Example: XMLConcat and XMLAgg

- the GROUP BY from Slide 495 can equivalently be expressed by using a (correlated) (Sub)query that returns a tuple for each country (consisting of the number and the aggregation of all cities):

```
SELECT XMLElement("Country",
  XMLAttributes(code AS code),
  XMLELEMENT(name, name),
  (SELECT XMLConcat(
     XMLElement("NoOfCities", count(*)),
     XMLAgg(XMLElement("city",name)))
   FROM City
   WHERE country=code))
FROM country;
```

[Filename: SQLX/xmlconcatagg.sql]

Constructed XML can then be used for filling tables:

FILLING A TABLE ... WITH XML ROW VALUES

```
CREATE TABLE CountryXML OF XMLType;

INSERT INTO CountryXML
(SELECT XMLElement("Country",
  XMLAttributes(code AS "Code",
                population AS "Population"),
  XMLElement("Name",name),
  (SELECT XMLElement("Capital",
            XMLForest(name AS "Name",
                      population AS "Population"))
   FROM city
   WHERE country=country.code
     AND city.name=capital))
FROM country);
```

[Filename: SQLX/fillcountry.sql]

FILLING A TABLE: XML COLUMN VALUES

```
CREATE TABLE CityXML
   (name XMLType,
    province VARCHAR2(32),
    country VARCHAR2(3),
    population XMLType,
    coordinates XMLType);

INSERT INTO CityXML
(SELECT XMLElement("name",name),  province, country,
  XMLElement("population", XMLAttributes(95 as year), population),
  CASE WHEN longitude IS NULL THEN NULL
       ELSE XMLElement("coordinates",
              XMLElement("longitude", longitude),
              XMLElement("latitude", latitude))
   END
 FROM city);
```

[Filename: SQLX/fillcity.sql]

HANDLING XML DATA FROM WITHIN SQL

- recall: XMLType is defined as an abstract datatype.
- it also has *selectors* that provide an interface for standard XML languages
- signature:

  extract: XMLType $\times$ XPath_Expression $\rightarrow$ XMLType $\cup$ string
  extractValue: XMLType $\times$ XPath_Expression $\rightarrow$ string
  existsNode: XMLType $\times$ XPath_Expression $\rightarrow$ Boolean
- implementation based on user-defined object types
  - cf. object-relational extensions to SQL
- above operations also available as member methods

```
SELECT extract(value(m), '//city[name="Berlin"]') FROM mondial m;
SELECT m.extract('//city[name="Berlin"]') FROM mondial m;
SELECT extractValue(value(m), '//country[@car_code="D"]/population')
FROM mondial m;
SELECT m.extractValue('//country[@car_code="D"]/population')
FROM mondial m;   -- buggy!!!
```

SELECT: “Extract” Function

extract(XMLType_instance, XPath_string)
XMLType_instance.extract(XPath_string)

First argument: selects an attribute with value of type “XMLType” in the current row (use value(.) function)
Second argument: applies XPath_string to it
Result: value of type XMLType or any other SQL type
(multi-valued results are concatenated)

XML Row Values

Value of the row is of type XMLType: apply methods directly

```
SELECT extract(value(c), '/Country/@Code'),
       extract(value(c), '/Country/Capital/Name')
FROM CountryXML c;

SELECT c.extract('/Country/@Code'),
       c.extract('/Country/Capital/Name')
FROM CountryXML c;
```


SELECT: “Extract” Function (Cont'd)

XML Column Values

Recall:

```
CREATE TABLE CityXML (name VARCHAR2(32),
     population XMLType, coordinates XMLType);
```

CityXML.population is an XMLType column object:

```
SELECT extract(population,'/') FROM CityXML;
SELECT c.population.extract('/') FROM CityXML c;
SELECT name, extractValue(population,'/population/@YEAR'),
       extractValue(population,'/population')
FROM CityXML;
SELECT name, c.population.extract('/population/@YEAR').getNumberVal(),
       c.population.extract('/population/text()').getNumberVal()
FROM CityXML c
ORDER BY 3;
```

- exact capitalization in XPath argument!
- extractValue currently not implemented as member method (bug)
- use getNumberVal() and getStringVal() functions

SUBQUERIES TO XMLTYPE IN THE WHERE CLAUSE

... for selecting and comparing values, use also extract():

```
SELECT name
FROM CityXML c
WHERE c.population.extract('/population/text()')
        .getNumberVal() > 1000000;

SELECT c.extract('/Country/Name/text()')
FROM CountryXML c
WHERE c.extract('/Country/@Population')
        .getNumberVal() > 1000000;
```

- Note: comparison takes place on the SQL level (WHERE)
  (→ join functionality when variables are used).
- Note: if the XPath expression returns a sequence of results, these are concatenated already during the evaluation of the extract() function ...
- ... thus, one has to use another way.

WHERE: "ExistsNode" Function

existsNode(XMLType_instance, XPath_string)

Checks if item is of XMLType_instance, and XPath_string has a nonempty result set:

```
SELECT name, extractValue(population,'/')
FROM CityXML
WHERE existsNode(population,'/population[text()>1000000]') = 1;

SELECT name, extractValue(population,'/')
FROM CityXML c
WHERE c.population.existsNode('/population[text()>1000000]') = 1;
```

UPDATING XML DATA

- the complete XMLType value is *changed*, not updated
- updateXML(...) as a (transformation) function!
  Note: the statement "SELECT updateXML(...) FROM ..." does not update the DB, but returns the value that would result from the update.

  updateXML(XMLType_instance, XPath_string, new_value)
- first argument: SQL – selects an (SQL-)attribute of the current tuple (must result in an XMLType object),
- $2n$th argument: selects the node(s) to be modified by the value of the ...
- $2n + 1$th argument: new value,
- result: updates instance of type XMLType.
- Note: the expression "SELECT updateXML(...) FROM ..." does not change the database but returns only the value that *would* result from the update.

Updating XML Data (Cont'd)

```
SELECT updateXML(c.population,
                 'Population/text()','1000000',
                 'Population/@YEAR','2004')
FROM CityXML c WHERE name='Gottingen';

SELECT updateXML(value(c),
                 '/Country/Name/text()','Fidschi')
FROM CountryXML c
WHERE extractValue(value(c),'Country/Name')='Fiji';
```

[Filename: SQLX/updatexml.sql]

Updating XML Data (Cont'd)

This function is then used in the SQL SET-Statement:

```
UPDATE CityXML c
SET c.population   -- an XMLType element
    = updateXML(c.population,
                '/population/text()','1000000',
                '/population/@YEAR','2004')
WHERE name='Gottingen'

UPDATE CountryXML c
SET value(c) = updateXML(value(c),
                '/Country/Name/text()','Fidschi')
WHERE existsNode(value(c),'/Country[Name="Fiji"]') = 1
```


12.3 Background: XMLType as Object Type

(cf. "Practical Training in SQL" course)

Since SQL3 Standard: Object(-relational) types

- user-definable: CREATE TYPE AS OBJECT ... / CREATE TYPE BODY
- stored as *row* or *column objects*
  CREATE TABLE cities OF CityObjectType;
- *member methods*
  - programmed in PL/SQL or recently also in Java
  - calls are embedded into SQL: SELECT *object.method(args)*
- reference attributes:
  CREATE TABLE COUNTRY (..., capital REF CityType, ...);
  SELECT c.capital ...;

⇒ now used for implementing XMLType

- as predefined internal classes/types
- can be used high-level from SQL, or low-level inside PL/SQL

XSLT IN ORACLE: "TRANSFORM" MEMBER METHOD

Member Method of XMLType: *XML-instance*.transform(*Stylesheet-as-XMLValue*)
as SQL function: SELECT XMLTransform(*XML-instance*,*Stylesheet-as-XMLValue*)

```
CREATE TABLE stylesheets
 (name VARCHAR2(100),
  stylesheet XMLTYPE);

INSERT INTO stylesheets VALUES('mondial-simple.xsl',
 system.getxml('http://www.dbis.informatik.uni-goettingen.de' ||
   '/Teaching/DBP/XML/mondial-simple.xsl'));

SELECT value(m).transform(s.stylesheet)
FROM mondial m, stylesheets s
WHERE s.name = 'mondial-simple.xsl';

SELECT XMLTransform(value(m),s.stylesheet)
FROM mondial m, stylesheets s
WHERE s.name = 'mondial-simple.xsl';
```

[Filename: SQLX/applystylesheet.sql]

Using built-in DOM, Parser, and XSL Engine

Tools from several packages can be explicitly used inside PL/SQL procedures:

- dbms_xmldom: implements DOM (usually, XML is transformed into DOM for processing it in detail)
  PL/SQL call: dbms_xmldom.*dosomething*(*object,args*)
- dbms_xmlparser: parses documents from CLOB or URL, parses DTD from CLOB or URL (and stores the result);
  access to the DOM instance/DTD in the parser then by "getdocument" or "getdoctype"
- dbms_xslprocessor: processxsl(*different arguments*);
  clob2file/file2clob allows for reading/writing;
  selectnodes/selectsinglenode/valueof: XPath queries

... for details: Oracle Documentation, google ...

```
CREATE OR REPLACE FUNCTION xslexample RETURN CLOB IS
  xmldoc      CLOB;
  xsldoc      CLOB;
  myParser    dbms_xmlparser.Parser;
  indomdoc    dbms_xmldom.domdocument;
  xsltdomdoc  dbms_xmldom.domdocument;
  xsl         dbms_xslprocessor.stylesheet;
  outdomdocf  dbms_xmldom.domdocumentfragment;
  outnode     dbms_xmldom.domnode;
  proc        dbms_xslprocessor.processor;
  html        CLOB;
BEGIN
  -- Get the XML document as CLOB
  SELECT value(m).getClobVal() INTO xmldoc FROM mondial m;
  -- Get the XSL Stylesheet as CLOB
  SELECT s.stylesheet.getClobVal() INTO xsldoc
  FROM stylesheets s WHERE name='mondial-simple.xsl';

  -- Get the new xml parser instance
  myParser := dbms_xmlparser.newParser;
  -- Parse the XML document and get its DOM
  dbms_xmlparser.parseClob(myParser, xmldoc);
  indomdoc := dbms_xmlparser.getDocument(myParser);

  -- Parse the XSL document and get its DOM
  dbms_xmlparser.parseClob(myParser, xsldoc);
  xsltdomdoc := dbms_xmlparser.getDocument(myParser);

  xsl  := dbms_xslprocessor.newstylesheet(xsltdomdoc, '');
  -- Get the new xsl processor instance
  proc := dbms_xslprocessor.newProcessor;

  -- Apply stylesheet to DOM document
  outdomdocf := dbms_xslprocessor.processxsl(proc, xsl, indomdoc);
  outnode    := dbms_xmldom.makenode(outdomdocf);

  -- Write the transformed output to the CLOB
  dbms_xmldom.writetoCLOB(outnode, html);
  -- Return the transformed output
  return(html);
END;
/
```

[Filename: OraXML/xslexample.sql]

12.4 Storing XML Data in Database Systems

- "shredding" and distributing over suitable tables (of object-relational object types) (queries are translated into SQL joins/dereferencing)
  - Schema-based
  - Generic mapping of the graph structure
- storing it as VARCHAR, CLOB (Character Large Object), or as separate file with special functionality
- storing it "natively"/model-based: internal object model

Literature

Klettke/Meyer "XML & Datenbanken" (dpunkt-Verlag), Ch. 8
Schöning: "XML und Datenbanken" (Hanser), Ch. 7,8
Chaudhri/Rashid/Zicari: XML Data Management

12.4.1 Mapping XML → Relational Model

two basic approaches:

- Schema-based: one or more "customized" tables for each element type
  (→ similar to relational normalization theory)
  - (possibly) many null values
  - efficient access on data that belongs together
- one generic large table based on the graph structure:
  (element-id, name of the property, value/id of the property)
  - no null values
  - although memory-consuming (keys/names that are stored once in (1) are now stored for each occurrence)
  - data that belongs together is split over several tuples

⇒ in both cases, theory and efficiency of relational database systems can be exploited.

SCHEMA-BASED STORAGE

necessary: DTD or XML Schema of the instance.

1. For each element type that has children or attributes, define a table that contains
   - a column that holds the primary key of the parent,
   - a primary key column if the element type has a member that satisfies (1) or (2),
   - for each scalar attribute and child element type with text-only contents that appears at most once, a column that holds the text contents.
2. for each multi-valued attribute or text-only subelement type that occurs more than once for some element type, a separate table is created with the following columns:
   - key of the parent node,
   - the (attribute or text) value

   (similar to 1:n relationships in the relational model).

- for mixed content: possible solutions depend on the specific structure
- special treatment for infrequent properties (to avoid nulls): handling in a separate XMLType column that holds all these properties together.

Schema-Based Storage: Example

For Mondial countries, provinces and cities, the following relations are created:

- country: key(mondial), key, name, code, population, area, ...
- border: ref(country), ref(other country), length
- language: ref(country), language, percentage
- province: ref(country), key, name, population, area
- city: ref(country), ref(province), key, name, longitude, latitude
- city-population: ref(city), year, value

Exercise

- give an excerpt of the instance
- translate some XPath/XQuery queries to SQL
- extended exercise: generate and populate the schema in SQL

Supported: Oracle (with augmented XML Schema), IBM DB2 (with DAD – Data Access Definition), MS SQL Server (extended Data-Reduced XML)

OBJECT-RELATIONAL APPROACH: INTERNAL OBJECT TYPES

- "shredded storage" of XML data is in general not implemented by plain relational tables, but using object-relational technology:
  object types, collections, varrays etc ...
- collections/varrays: with value- and path indexes
- XPath expressions are rewritten into these structures

Integration of "legacy" object types

- application-dependent object types (as used in SQL3 in pre-XML times): standard mapping to XML (e.g. for data exchange)

Oracle & XML Schema

... register XMLSchema (must be typed in one single line!)

```
EXEC dbms_xmlschema.registerURI('http://mondial.de/m.xsd',
         'http://dbis.informatik.uni-goettingen.de/Mondial/mondial.xsd');
```

can be deleted with

```
EXEC dbms_xmlschema.deleteSchema('http://mondial.de/m.xsd',
      dbms_xmlschema.DELETE_CASCADE_FORCE);
```

- ... now, it knows http://mondial.de/m.xsd and created object tables for all root element types:
  SELECT * from ALL_XML_TABLES;

```
CREATE TABLE mondial2 OF XMLType
 XMLTYPE STORE AS OBJECT RELATIONAL
 XMLSCHEMA "http://mondial.de/m.xsd"
 ELEMENT "mondial";

INSERT INTO mondial2 VALUES(
system.getxml(
 'http://www.dbis.informatik.uni-goettingen.de/Teaching/DBP/XML/mondial.xml'));
SELECT XMLisValid(value(m)) FROM mondial2 m;
```


GRAPH-STRUCTURE-BASED STORAGE

Without any schema knowledge, the graph structure can be represented in a single large table:

NodeNumber	ParentNode	[SiblingNo if ordered]	Name	Value

(see next page)

Alternatives

- separate table for elements and attributes (without node number and sibling number)
- separate between no-value, string value and numeric values for storing adequate types.
- previous-sibling and following-sibling columns instead of sibling-no (DOM style)

Querying

- requires recursive queries (PL/SQL; CONNECT BY)
- large joins (using the same large table several times)
- not implemented in any commercial system [according to Schöning 2003]

NodeNumber	ParentNode	SiblingNo	Name	Value
1	doc	1	mondial	
2	1	1	country	
3	2		@code	D
4	2		@membership	ref(eu)
:	:		:	:
41	2		@membership	ref(un)
42	2		@area	356910
43	2		@capital	ref(92)
44	2	1	name	Germany
45	2	2	population	83536115
:	:		:	:
90	2	47	province	
91	90	1	name	Berlin
92	90	2	city	
93	92		@country	ref(2)
94	92	1	name	Berlin
95	92	2	population	
96	95		@year	1995
97	95		text()	3472009
:	:		:	:

12.4.2 “Opaque” Storage

XML documents are stored as a whole as special datatype that can be used as row type or column data type (most commercial DBS; as described above for SQL/XML)

- approaches with text-based storage (CLOBs, files)
- specialized functionality for this datatype
  (cf. object-relational DBs: member functions)
  - XPath querying, XSLT support
  - validation
  - text search functions
- syntax embedded into SQL
- supported by indexes
  - full text indexes
  - path indexes/ “functional” indexes (user-defined, e.g. over //city/@country)
  - application and refinement of classical algorithms
- optimization of queries below the relational level!

12.4.3 “Native” Storage

Using “original” concepts of the database for storing XML (internal XML or object model) instead of mapping it or “simply” representing it as ASCII.

- often based on existing object-oriented DB-systems with application of concepts from hierarchical and network-DBs
- no document transformation to another data model
- data model/classes based on the notions of “tree”, “element”, “attribute”, “document order”
- navigation
- XPath/XQuery/XSQL APIs

“Native” Storage: Systems and Products

Many early implementations came from the object-oriented area:

- XML-QL, based on the Strudel system
- LoPiX, based on F-Logic
- Lorel-XML, based on Lorel/OEM
- Tamino (Software AG, Darmstadt, founded 1969 (Adabas, hierarchical DB), Tamino 1999, with XQL, first native XML DBMS),
- Excelon (until 1998: ObjectDesign with “ObjectStore”; since 12.2002: acquired by Progress Software Corp.)
- POET (Hamburg, “Persistent Objects and Extended Database Technology”, product 1990, spin-off from BKS 1992, OQL interfaces, SGML Document Repository 1997, Content Management Suite since 1998, merger with Versant 2004)
- Infonyte (GMD IPSI XQL 1998, based on a “Persistent DOM”, 12.2000: spinoff TU Darmstadt/Fraunhofer-IPSI)

GENERIC DATABASE BEHAVIOR FOR XML DATABASES

Everything that has been developed and dicussed for relational databases is also relevant for XML:

- physical storage + storage management
- optimization, evaluation algorithms
- multiuser operation, transactions (ACID), safety, access control
- ECA-rules, triggers

The algorithms and theoretical foundations are very similar.

Often, relational (or hierarchical) DB technology is actually used inside.

COEXISTENCE OF XML AND RELATIONAL DATA

- generating XML (views, data exchange packets, ...) from stored relational data
- relational (and object-relational) techniques used for efficiently storing data-centric XML
- storing text-oriented data in RDB with specialized “native” datatypes
- XPath is also accepted by SQL/XML
- additional XML processing functionality by packages and object types
- XQuery is still not the “winner” for data-oriented applications!
- is it the winner for document-oriented applications?
  `http://www.w3.org/TR/xquery-full-text/`

Chapter 13
Miscellaneous

Shortcomings in this lecture

- XML: namespaces (used e.g. for XSL, XLink – but in this lecture really interesting only in combination with RDF)
- XML: processing instructions
- theory: XML Data Model, XPath/XQuery Formal Semantics
  (currently in an alignment process with XML Schema)

Application areas:

- Web Services
- Multimedia applications with XML
- Semantic Web